

Abstract

5 A fluid flow actuated downhole tool is configurable in at least a first tool configuration and a second tool configuration. The tool comprises a tubular housing and an activating sleeve, the housing being adapted to catch the sleeve when the sleeve is dropped from surface and the engagement of the sleeve with the housing permitting actuation of the tool between the first and second tool configurations. A flow restriction is provided for permitting fluid flow actuation of the tool when the activating sleeve has been caught in the body.

10031219.011502

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 January 2001 (25.01.2001)

PCT

(10) International Publication Number
WO 01/06086 A1

(51) International Patent Classification⁷: E21B 21/10

(21) International Application Number: PCT/GB00/02712

(22) International Filing Date: 14 July 2000 (14.07.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
9916513.6 15 July 1999 (15.07.1999) GB

(71) Applicant and

(72) Inventor: CHURCHILL, Andrew, Philip [GB/GB]; 11
McDonald Drive, Ellon, Aberdeen AB41 3BD (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published:

— With international search report.

(74) Agents: MCCALLUM, William, Potter et al.; Cruikshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DOWNHOLE BYPASS VALVE



(57) Abstract: A fluid flow actuated downhole tool is configurable in at least a first tool configuration and a second tool configuration. The tool comprises a tubular housing and an activating sleeve, the housing being adapted to catch the sleeve when the sleeve is dropped from surface and the engagement of the sleeve with the housing permitting actuation of the tool between the first and second tool configurations. A flow restriction is provided for permitting fluid flow actuation of the tool when the activating sleeve has been caught in the body.

10031219.011502

WO 01/06086 A1